



1. Dryseal Trim retaining bracket : HDL TRB200 @ 600mm centres
2. 4mm Insect gauze or mesh
3. Dryseal Trim : HDL H 0200 A
4. Anti-corrosive fixings where required
5. Dryseal flat sheet: HDL H 1250F
6. 19mm WBP plywood or OSB3 decking
7. 50x25mm timber batten @ 600mm centres
8. 25mm thick drip batten
9. Adhesive button
10. Dryseal trim: HDL H 0260 D
11. Roof joists
12. Insulation
13. 50x50mm timber counter batten

**Note:** In-situ laminate over fixings and seams/joints omitted for clarity. Please see drawing no: JFD for more detail.

1. Dryseal Trim retaining bracket : HDL TRB200 @ 600mm centres
2. 4mm Insect Gauze or mesh
3. Dryseal Trim : HDL H 0200 A
4. Anti-corrosive fixings where required
5. Dryseal flat sheet: HDL H 1250F
6. 19mm WBP plywood or OSB3 decking
7. 50x25mm timber batten @ 600mm centres
8. Dryseal Trim : HDL H 0150 G
9. Dryseal trim: HDL H 0260 D
10. Roof joists
11. Insulation

**Note:** In-situ laminate over fixings and seams/joints omitted for clarity. Please see drawing no: JFD for more detail.

DRAWING TITLE		
Typical Cold Roof Ventilated Parapet Detail		
PROJECT		
NA		
CLIENT		
HDL		
DRAWN	DATE	SHEET
DB	06.07.2016	01
SCALE	PAPER SIZE	REVISION
NTS	A3	NA
DRAWING NO		
VPARAWALLCR		
Hambleside Danelaw Ltd		
T 01327 701900		
F 01327 701909		
www.hambleside-danelaw.co.uk		
- All dimensions are in millimetres unless otherwise stated		
- All dimensions to be checked on site		
- Do not scale		
©Hambleside Danelaw Ltd, own the copyright of this document which is supplied in confidence, this document must not be used for any other purpose other than that it is supplied for.		
<b>DRYSEAL®</b>		